


DRUID



DESCENDER

223201

A lightweight, compact auto-braking descender for rope access and rescue designed for semi-static ropes ranging from 10-11 mm. Designed with an anti-panic function the body and lever are made of robust hot-forged aluminium alloy. The internal mechanism and locking cam use a patented design for smooth action on the rope which prevents rapid wear-and-tear and absorbs energy from small shocks with a slight amount of rope slippage.

RATING: 15kN

LIFESPAN:

CERTIFICATION:

EN 12841 C, EN 341 2A, EN 15151-1

EN 12841 C as a descender of the working line for workers up to 120 kg; can also be used for rope access rescue up to 200 kg.

EN 341 2A as an emergency evacuation device on a single line for workers up to 120 kg, 11 mm semi-static rope (Lithium 11 mm).

EN 15151-1 for climbing structures using mountaineering techniques with dynamic ropes ranging from 9.9 to 11 mm.



MODEL	SIZE	WEIGHT (G)	DIMENSIONS	MATERIAL	RATING (KG)
223201	9.9-11mm Rope	Max 280g	9.9-11mm Rope		15kN

PRODUCT FEATURES

- For rope diameter 9.9 to 11mm.
- Max rescue load of 200kg.
- Proprietary anti-panic function.
- Trigger activated cam.
- Mechanical parts made of stainless steel.
- Lever made of forged aluminium alloy.